

EXPRESS 250 and EXPRESS PLUS CUSTOM SIGN TEMPLATE - FRONT TOP

Match to PMS 158 Orange
NOR-COTE weatherable CMG ink

3M 5100 white reflective film



EXPRESS 250
and
EXPRESS PLUS

NOTES & REQUIREMENTS



- Artwork must be in **vector** format. Do not use raster images.
- Artwork must be in CMYK process color. (Call out any PMS numbers for reference, but artwork is screen printed using CMYK only.)
- Solid color only, no transparency or gradients
- For full bleed artwork, provide minimum 5-mm bleed
- Convert all fonts to outlines
- *ChargePoint artwork and notes are included as reference (ChargePoint Reference Artwork layer).

MATERIALS

- Total thickness 0.040" max: White styrene, 0.03" thick; 3M 5100 white reflective film; external laminate 0.002" thick ORAGUARD 290 PVC.
- NOR-COTE weatherable CMG ink over reflective material
- Finished label is ROHS compliant

ChargePoint standard artwork is included for reference only.

Place custom artwork on CUSTOMER ARTWORK layer:



EXPRESS 250 and EXPRESS PLUS CUSTOM SIGN TEMPLATE - FRONT BOTTOM

Match to PMS 158 Orange
NOR-COTE weatherable CMG ink

3M 5100 white reflective film
underneath



EXPRESS 250
and
EXPRESS PLUS

NOTES & REQUIREMENTS

- Artwork must be in **vector** format. Do not use raster images.
- Artwork must be in CMYK process color. (Call out any PMS numbers for reference, but artwork is screen printed using CMYK only.)
- Solid color only, no transparency or gradients
- For full bleed artwork, provide minimum 5-mm bleed
- Convert all fonts to outlines

*ChargePoint artwork and notes are included as reference (ChargePoint Reference Artwork layer).

MATERIALS

- Total thickness 0.040" max: White styrene, 0.03" thick; 3M 5100 white reflective film; external laminate 0.002" thick ORAGUARD 290 PVC.
- NOR-COTE weatherable CMG ink over reflective material
- Finished label is ROHS compliant

ChargePoint standard artwork is included for reference only.

Place custom artwork on CUSTOMER ARTWORK layer:

